



## **PRIME ULTRA SYNTHETIC BLEND MOTOR OIL**

### **DESCRIPTION**

**PRIME ULTRA SYNTHETIC BLEND MOTOR OIL** is a premium advanced formula automotive engine oil designed for vehicles operating under severe driving or extreme temperature conditions. **PRIME ULTRA SYNTHETIC BLEND MOTOR OILS** provide improved protection against deposit and sludge formation and outstanding wear protection to critical engine components for today's gasoline engines including E85 gasoline/ethanol blends.

**PRIME ULTRA SYNTHETIC BLEND MOTOR OIL** is fully licensed to meet or exceed the latest API SP service classification, ILSAC GF-6A, and the previous service classifications API SN Plus. They are suitable for use in 4-stroke gasoline engines in passenger cars and light trucks, power boats, motor cycles and other mobile and stationary equipment. They provide excellent service in high-revving engines in small cars and light trucks with today's gasoline and ethanol (up to E85) fuels and are suitable for use in turbocharged engines.

### **FEATURES**

- Excellent protection from deposits at all operating temperatures
- Meet or exceed new car warranty requirements for North American and Asian where ILSAC GF-6A or API SP engine oils are recommended.
- Meet or exceed ILSAC GF-6A requirements for fuel economy and fuel economy retention.
- Backwards compatible to the previous API SN, API SN Plus service categories.
- Protect against low speed pre-ignition (LPSI)
- Exceptional resistance to High Temperature Thermal Breakdown

### **APPLICATIONS**

#### **Recommended for the following applications:**

- Where API-SP, API SN Plus, API SN-RC, API SN oils are required.
- Where ILCAS GF-6A, GF-5 oils are required.
- Where Ford WSS-M2C960-A1, Ford WSS- M2C961-A1 oils are required.
- Where Chrysler MS-6395 oils are required.
- Meets Asian OEM performance requirements including Honda, Hyundai, Kia, Mazda and Toyota.

## TECHNICAL DATA

<b>SAE GRADE</b>	<b>5W-20 SYNTHETIC BLEND</b>	<b>5W-30 SYNTHETIC BLEND</b>
Viscosity cSt @ 40°C	48.2	68.9
Viscosity cSt @ 100°C	8.6	11.3
Viscosity Index	156	158
API Gravity	34.8	34.7
Pour Point °F	-49	-49
Base Number, ASTM D2896	7	7
API: RC *Resource Conserving*	YES	YES
LSPI Protection	Yes	Yes
ILSAC GF-6A Certified	YES	YES
API Licensed Service	API SP, SP Resource Conserving	API SP, SP Resource Conserving

Prime Lube, Inc. 800 Roosevelt Ave., Carteret, NJ 07008

Phone: (800) 634-4615