



## ***PRIME PLUS 5W-20, 5W-30 and 10W-30 MOTOR OIL***

### ***DESCRIPTION***

**PRIME PLUS MOTOR OIL** is a synthetic blend multi-grade motor oil formulated to protect against sludge, varnish, rust, and harmful deposits and is designed to promote cleaner running engines. **PRIME PLUS MOTOR OIL** helps reduce friction and is fully licensed to meet and exceed the latest API SP-Resource Conserving classification, ILSAC GF-6A, and the previous service classifications API SN-RC, SM, SL, SJ, and ILSAC GF-5.

### ***APPLICATIONS***

**PRIME PLUS MOTOR OIL** provides excellent service in today's high-revving engines and is recommended for use in gasoline and ethanol (up to E85) fueled passenger cars and light trucks, power boats, 4-stroke motor cycles and other mobile and stationary equipment. It is fully compatible, and may be mixed, with other synthetic and conventional gasoline engine lubricants.

### ***FEATURES***

- Excellent protection from deposits at all operating temperatures
- Excellent anti-wear, anti-foaming, anti-rust and corrosion protection
- Energy Savings – API Resource Conserving designation
- Cleaner Running Engines
- Protects against low-speed pre-ignition (LPSI).

### ***APPLICATIONS***

#### **Recommended for the following applications:**

- Exceeds the requirements of API SP, API SP-Resource Conserving and all previous categories.
- Exceeds the requirements of ILSAC GF-6A and ILSAC GF-5.
- When Ford WSS-M2C945-A (5W-20), Ford WSS- M2C946-A, General Motors GM 6094M (5W-20, 5W-30) or Fiat 9.5535 CR-1 (SAE 5W-30) performance is required.
- When Chrysler MS 6395 is required.

## TECHNICAL DATA

<i>SAE GRADE</i>	<i>PRIME PLUS 5W-20</i>	<i>PRIME PLUS 5W-30</i>	<i>PRIME PLUS 10W-30</i>
Viscosity @ 40°C	41.7	64.8	68.6
Viscosity @ 100°C	8.7	10.9	10.5
Viscosity Index	149	160	141
Pour Point °F	-48	-45	-39
API Resource Conserving	Yes	Yes	Yes
LPSI Protection	Yes	Yes	Yes

**Prime Lube, Inc. 800 Roosevelt Ave., Carteret, NJ 07008**

**Phone: (800) 634-4615**