



**PRIMEPLUS ATF** is a premium automatic transmission fluid that is designed and recommended for use in automatic transmissions previously serviced by GM DEXRON®-III (H) and FORD MERCON® brands. It may also be used in equipment requiring a “Type A” ATF fluid, Allison C-4, Caterpillar TO-2 and Ford specifications M2C138-CJ and M2C166-H.

**PRIMEPLUS ATF** is formulated to provide:

- Superior wear protection
- Excellent frictional properties for smooth shifting
- Excellent anti-shudder performance
- Excellent protection against varnish and sludge formation
- Excellent seal compatibility
- Excellent low-temperature performance
- Excellent thermal stability and oxidation resistance

**PRIMEPLUS ATF** 's state-of-the-art additive system and premium quality Group II base oil provides excellent protection and peak performance in passenger cars, SUV's and light duty trucks. **PRIMEPLUS ATF** is not recommended for use in transmissions requiring GM DEXRON®

<u>PROPERTY</u>	<u>TYPICAL SPEC.</u>
FLASH POINT, COC C° (F°)	212 (413)
POUR POINT, C° (F°)	-52 (-61)
DENSITY, g/cm <sup>3</sup> ® 15° C	0.860
VISCOSITY, cSt	
@ 40 C	35.4
@ 100 C	7.2
VISCOSITY, Cp	
@ -20° C	1300
@ -30° C	4200
@ -40° C	17000
VISCOSITY INDEX	172
COLOR	RED
FOAM TEST, ASTM D892	PASS

