FULL SYNTHETIC
MULTI-VEHICLE ATF

DESCRIPTION

PRIME ULTRA Full Synthetic Multi-Vehicle Automatic Transmission Fluid (MV ATF) is a premium, low-viscosity transmission fluid formulated for a wide range of planetary-gear automatic transmissions. Its advanced full synthetic formulation provides protection against wear and transmission shudder while maintaining friction stability for smooth, consistent shifting. Engineered to resist thickening at elevated temperatures, PRIME ULTRA MV ATF delivers dependable performance under demanding driving conditions. Suitable for applications requiring GM DEXRON®-VI, Ford MERCON® LV, and a broad range of compatible domestic and imported automatic transmission specifications.

MEETS THE PERFORMANCE REQUIREMENTS OF:

- **General Motors:** DEXRON®-VI; earlier DEXRON®-III G/H and DEXRON®-II applications.
- **Ford:** MERCON® LV, MERCON® and applicable Ford ATF specifications.
- **Toyota / Lexus:** Toyota T-II, T-III, T-IV, WS; JWS 3309.
- **Honda / Acura:** Honda ATF DW-1 and Z-1.
- **Nissan / Infiniti:** Nissan Matic-D, J, K and S.
- **Hyundai / Kia / Mitsubishi:** SP-II, SP-III, SP-IV and applicable Diamond ATF specifications.
- **Chrysler / Dodge / Jeep:** Selected Chrysler 8- and 9-speed automatic transmission applications, AS68RC and NAG-1.
- **European Applications:** Selected BMW, Mercedes-Benz, Audi, Volkswagen, Volvo and ZF automatic transmission specifications.

PERFORMANCE ATTRIBUTES

- **Full Synthetic Technology:** Formulated with advanced synthetic technology to deliver dependable automatic transmission performance across a wide range of operating conditions.
- **Wear Protection:** Helps protect critical transmission components against wear under demanding operating conditions.
- **Shudder Protection:** Helps minimize transmission shudder to support smoother operation and improved driving comfort.
- **Friction Stability:** Maintains consistent frictional performance to support smooth, reliable shifting throughout operation.
- **Thermal Stability:** Resists fluid thickening at elevated operating temperatures to help maintain consistent transmission performance.
- **Multi-Vehicle Versatility:** Engineered for a broad range of domestic and imported planetary-gear automatic transmissions requiring compatible ATF specifications.

PRODUCT DATA	TYPICAL VALUES *
Viscosity @ 40°C, cSt	28.56
Viscosity @ 100°C, cSt	5.797
Brookfield Viscosity @ -40°C, cP	10,300
Viscosity Index	151
Pour Point	-60°F
Specific Gravity @ 60°F (15.6°C)	0.8468
API Gravity, °API	35.6°
Color	Red

*Typical values are representative and are not intended as manufacturing specifications.

Available Packaging: Gallon, 5 Gallon Pail, 16 Gallon Keg, 55 Gallon Drum, 275 Gallon Tote, BULK.
Packaging availability may vary by product grade and location. 31136 160 PAIL | 31136 020 DRUM | 31136 001 BULK

ADDITIONAL INFORMATION

Handling & Storage: Store in a clean, dry area. Keep containers tightly sealed when not in use. Refer to SDS for safety information.
SDS# 18122.

"The Lubricant Experts"
800-634-4615 | 1-732-969-9200
800 Roosevelt Avenue, Carteret, NJ 07008
www.primelubeinc.com

PERFORMANCE YOU CAN TRUST.
SOLUTIONS YOU CAN COUNT ON
PREMIUM LUBRICANTS

DC# T18122 **REV:** 20261106
PRIME LUBE®, PRIME PLUS®, and PRIME ULTRA® are registered trademarks of Prime Lube®

FULL SYNTHETIC
MULTI-VEHICLE ATF

RECOMMENDED APPLICATIONS & SPECIFICATIONS

GENERAL MOTORS / ALLISON
- GM DEXRON®-VI, DEXRON®-III G/H, DEXRON®-II
- GMN10060
- Allison C-3, C-4, TES-389
- Saturn T-IV, GM TASA, GM WS ATF
- Saturn P/N 21005966

FORD / LINCOLN / MERCURY
- MERCON® LV (XT-10-QLV)
- MERCON®
- Ford FNR5
- Ford M2C138-CJ, M2C166-H, M2C922-A1, M2C924-A
- Ford ESP-M2C166-H
- Ford XT8QAW

CHRYSLER / DODGE / JEEP / MOPAR
- Chrysler 8- and 9-speed transmissions*
- Chrysler AS68RC
- Chrysler P/N 05127382AA, 68043742AA
- Mopar AS68RC, JWS 3309
- Mopar NAG-1

TOYOTA / LEXUS / SCION
- Toyota ATF T-II, T-III, T-IV, WS
- Toyota D-II, D-III
- JWS 3309, JWS 3324
- Lexus JWS 3309
- Scion applications

HONDA / ACURA
- Honda ATF DW-1
- Honda ATF Z-1

NISSAN / INFINITI
- Nissan Matic-D, J, K, S

HYUNDAI / KIA / MITSUBISHI
- Hyundai/Kia SP-II, SP-III, SP-IV
- Hyundai/Kia SP-IV M, SP-IV RR
- Hyundai/Kia RED-1
- Hyundai/Kia Dex-II/SP-II, JWS 3314, 9683
- Hyundai NSWS9638
- Mitsubishi Diamond SP-II, SP-III
- Mitsubishi MA-1
- Mitsubishi DiaQueen SK, AW, J2, J3, PA

BMW / MINI
- BMW 7045E, LA2634, LT71141
- BMW JWS 3309
- BMW ZF 5HP18FL, 5HP24, 5HP30
- BMW ETL-7045E, ETL-8072B
- BMW P/N 83 22 0 0246 922
- BMW P/N 83 22 0 024 359
- BMW P/N 83 22 0 403 249
- BMW P/N 83 22 9 407 765
- BMW P/N 83 22 9 407 807
- MINI T-IV, P/N 83 22 0 402 413

MERCEDES-BENZ
- MB 223.2
- MB 236.1, 236.2, 236.5, 236.6, 236.7
- MB 236.8, 236.9, 236.10, 236.12, 236.41

AUDI / VOLKSWAGEN
- Audi 5HP LT71141
- Audi G 052 025, G 052 162, G 055 025
- Audi G 052 162-A1/A2, G 052 025-A2
- VW G 052 025, G 052 162, G 052 099, G 055 025
- VW G 055 025-A2
- VW P/N GUS 000 162
- VW TL 52162 (LT71141)
- VW ZF 5HP18FL, 5HP19FL, 5HP24, 5HP30

ZF TRANSMISSIONS
- ZF 845RE, 870RE
- ZF 8HP45, 8HP70, 8HP90
- ZF 3- and 4-speed transmissions
- ZF TE-ML 02F, 03D, 04D, 09, 11A
- ZF TE-ML 14A, 14B, 14C, 16L, 17C

JAGUAR / LAND ROVER
- Jaguar ATF 3403 M115
- Jaguar LT71141, ZF 5HP24
- Jaguar JLM20238
- Jaguar P/N WSS-M2C922-A-1

VOLVO
- Volvo passenger car 4- and 6-speed applications
- Volvo 97340, 97341, 97342
- Volvo P/N 1161540-8

MAZDA
- Mazda ATF D-II, M-III, M-V
- Mazda ATF FZ, F-1, S-1, N-1
- Mazda ATF 3317, T-IV

SUBARU / SUZUKI
- Subaru ATF 5AT, ATF-HP
- Subaru Dex II, AT OIL 5D06
- Suzuki ATF 2326, 2384K
- Suzuki JWS 3309, 3314

PORSCHE
- Porsche P/N 999 917 547 00 (A2)
- Porsche ZF 5HP19FL, ZF 5HP20
- Porsche LT71141, ATF 3403-M115
- Porsche T-VI, JWS 3309

OTHER EUROPEAN APPLICATIONS
- Peugeot ZF 4HP20
- Opel applications*
- Saab P/N 22 717 466, 93 165 147 (AW-1)
- Fiat T-VI, JWS 3309
- Esso LT71141
- Shell 3403, 3403 M115, LA2634
- Texaco 7045-E, N402
- Fuchs 3353

COMMERCIAL / INDUSTRIAL TRANSMISSIONS
- Caterpillar CAT TO-2
- MAN 339 Type V1, V2, Z1, Z2
- Voith 55.6335 (G607)
- Hino Blue Ribbon ATF
- FUSO ATF-II, SP-III, A4

ADDITIONAL ASIAN / INTERNATIONAL APPLICATIONS
- Isuzu BESCO ATF-II, ATF-III
- Isuzu P/N 08200-9001 / Genuine ATF
- Idemitsu APOROIL ATF HP
- Daewoo LT71141
- Daihatsu AMMIX ATF D-II, D-III SP
- JASO M315-2013 1A, 1A-LV, 2A
- JASO M315-2004 1A, 2A
- JWS 3309, JWS 3324
- Type A

*IMPORTANT APPLICATION NOTE
The above references are provided for application review. They do not independently establish OEM approval or licensing.

"The Lubricant Experts"
800-634-4615 | 1-732-969-9200
800 Roosevelt Avenue, Carteret, NJ 07008
www.primelubeinc.com

PERFORMANCE YOU CAN TRUST.
SOLUTIONS YOU CAN COUNT ON
PREMIUM LUBRICANTS

DC# T18122 **REV:** 20261106
PRIME LUBE® , PRIME PLUS® , and PRIME ULTRA® are registered trademarks of Prime Lube®